




linear dimension(Tolerances Standard GB/T 14486-2008)								—	\square	\perp
variable range	to 6	over 6	over 10	over 30	over 60	over 100	over 160	to 10	over 10	over 100
		to 10	to 30	to 60	to 100	to 160	to 100		to 100	
tolerance	± 0.20	± 0.30	± 0.50	± 0.70	± 1.00	± 1.30	± 1.60	0.10	0.30	0.60



REVISION RECORD				
REV.	DESCRIPTION	ECN NO.	APPROVE	DATE
A	新发行		YXW	2015. 5. 15

UL/CUL 技术参数 UL/CUL Technical Data			
等级 Use Group	B	C	D
额定电压 Rated Voltage (V)	300	-	300
额定电流 Rated Current (A)	8	-	10
接线范围 Wire Range 单/多芯线 Solid/Stranded (AWG)	28-16		
耐电压 withstanding VOLTAGE	1600V/Min		
IEC 技术参数 IEC Technical Data			
过电压类别 Overvoltage Category	III	II	I
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage (V)	-	160	320
额定电流 Rated Current (A)	-	7	7
额定冲击电压 Impulse Withstand voltagea (KV)	-	2.5	2.5
导线截面积 Conductor cross section 硬质/柔性导线 Solid/flexible (mm ²)	1.5		
材 料 Material			
绝缘材料 Insulation Material	PA66		
阻燃等级 Lmflammability	UL94V-0		
导体材料 Contactor Material	铜合金 Copper alloy		
导体表面镀层 Contactive Coating	镀镍 Ni plated		
一般参数 Other Data			
间距 Pitch (mm)	3.81		
极 数 Poles (P)	2-24		
剥线长度 Stripping Length (mm)	8-9		
螺丝 Screw/扭矩 Torque (Max) (N. M)	M2/2.0		
工作温度 Operating temperatur (° C)	-40--+105		
引针尺寸 Pin Dimensions (mm)	--		
PCB板孔径 PCB Hole Diameter (mm)	--		

DES.	CLB	DATE	2015. 2. 25	单位/UNITS	MM	时间/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	A
CHK.	LF	DATE	2015. 2. 25	宁波市旭骋电子有限公司 NINGBOSHI XUCHENG ELECTRONIC CO., LTD				名称/TITLE	XC15EDGKM-3.81			
APP.	YXW	DATE	2015. 2. 25									